



Model with basic equipment. Also useable as a heavy-duty electric strike.

#### Overview of Advantages

- Radius keep, FaFix®, adjustable by 3 mm
- Universal voltage
- Screw-in Terminal / plug-in connection
- Compatible with DIN 18250 mortise locks
- Compatible with ProFix® 2 striking plates
- Optimum slindig ramp for a soft interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

#### Scope of delivery

- 1 piece electric strike

#### Technical data

Voltage	10-24 V AC/DC
Adjustable latch (FF, FaFix®)	Yes
Bi-directional diode	Yes
Fail-locked	Yes
Break-in resistance	9000 N
Height	66 mm
Width	20,1 mm
Depth	25,5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	6 mm
Operating temperature range	-15 °C to +40 °C
Load cycles for in-plant test	250000
Installation position	vertical and horizontal
Suitability for fire protection	Yes
Test certificate number	P-120003624
Certified in compliance with	DIN EN 14846
Continuous duty	11-13 V DC
Rated resistance	43,00 Ω
Rated current consumption 12 V DC	280 mA
Rated current consumption 24 V DC	560 mA
Rated current consumption 12 V AC	250 mA
Rated current consumption 24 V AC	500 mA
Max. latch preload AC	200 N
Max. latch preload DC (stabilised)	50 N

#### Article number

118F.13-----A71

